



Heated Towel Rails

Jersey Square 4 BAR

Product Code MS4 | MS4 BLACK | MS4 BSS MS4 GM | MS4 BRASS


Dimensions (mm) 620(w) x 500(h) x 120(d)mm

Width Centres **595mm** Vertical Centres **300mm**




Finishes: Beautiful and highly durable palette of exquisite finishes

(Polished Stainless/Black/Brushed Stainless/Brushed Gunmetal/Brushed Brass)



Features

- 4 bars
- Dual wired-can connect from LH or RH bottom leg
- Concealed wiring kit included
- All fixing accessories included
- 40watts, 230-240 Volts,50 Hz single phase
- Class 1 appliance requires an earth connection
- Ingress Protection Rating IP45
 Splashproof



Notes: Wiring connection is either LH or RH bottom leg and can be a concealed or exposed connection. It should be positioned at least 600mm above the floor.





Heated Towel Rails

Jersey Square 7 BAR

Product Code MS7 | MS7 BLACK | MS7 BSS MS7 GM | MS7 BRASS

Dimensions (mm) 620w) x 920(h) x 120(d)mm


Width Centres **595mm** Vertical Centres **720mm**



POLISHED MS7


Finishes: Beautiful and highly durable palette of exquisite finishes

(Polished Stainless/Black/Brushed Stainless/Brushed Gunmetal/Brushed Brass)



Features

- 7 bars
- Dual wired-can connect from LH or RH bottom leg
- Concealed wiring kit included
- All fixing accessories included
- 80watts, 230-240 Volts,50 Hz single phase
- Class 1 appliance requires an earth connection
- Ingress Protection Rating IP45
 Splashproof



Notes: Wiring connection is either LH or RH bottom leg and can be a concealed or exposed connection. It should be positioned at least 600mm above the floor.





Heated Towel Rails

Jersey Square 10 BAR

Product Code MS10 | MS10 BLACK | MS10 BSS MS10 GM | MS10 BRASS

Dimensions (mm) 620(w) x 1340(h) x 120(d)mm

Width Centres **595mm** Vertical Centres **1140mm**




Finishes: Beautiful and highly durable palette of exquisite finishes

(Polished Stainless/Black/Brushed Stainless/Brushed Gunmetal/Brushed Brass)



Features

- 10 bars
- Dual wired-can connect from LH or RH bottom leg
- Concealed wiring kit included
- All fixing accessories included
- 110watts, 230-240 Volts,50 Hz single phase
- Class 1 appliance requires an earth connection
- Ingress Protection Rating IP45 Splashproof



Notes: Wiring connection is either LH or RH bottom leg and can be a concealed or exposed connection. It should be positioned at least 600mm above the floor.