





Executive Round

Product Code HTR-TR0601

Dimensions (mm) 520(w) x 680(h) x 120(d)mm


Width Centres 485mm Vertical Centres 480mm



Features

- 6 bars
- Dual wired-can connect from LH or RH bottom leg
- Concealed wiring kit included
- All fixing accessories included

- 50watts, 230-240 Volts,50 Hz single phase
- Class 1 appliance requires an earth connection
- Ingress Protection Rating IP45 Splashproof









Executive Round

Product Code HTR-TR0602

Dimensions (mm) 850(w) x 680(h) x 120(d)mm


Width Centres 820mm Vertical Centres 480mm



Features

- 6 bars
- Dual wired-can connect from LH or RH bottom leg
- Concealed wiring kit included
- All fixing accessories included

- 80watts, 230-240 Volts,50 Hz single phase
- Class 1 appliance requires an earth connection
- Ingress Protection Rating IP45 Splashproof









Executive Round

Product Code HTR-TR0801/ HTR-TR0801 BSS/ HTR-TR0801 GM

Dimensions (mm) 600(w) x 920(h) x 120(d)mm

Width Centres 567mm Vertical Centres 720mm


Finishes: Beautiful and highly durable palette of exquisite finishes (Polished Stainless/Brushed Gunmetal)

Features

- 8 bars
- Dual wired-can connect from LH or RH bottom leg
- Concealed wiring kit included
- All fixing accessories included

- 80watts, 230-240 Volts,50 Hz single phase
- Class 1 appliance requires an earth connection
- Ingress Protection Rating IP45 Splashproof











Executive Round

Product Code HTR-TR1101/HTR-TR1101 BSS/ HTR-TR1101 GM

Dimensions (mm) 600(w) x 1280(h) x 120(d)mm

Width Centres 567mm Vertical Centres 1080mm


Finishes: Beautiful and highly durable palette of exquisite finishes (Polished Stainless/Brushed Gunmetal)

Features

- 11 bars
- Dual wired-can connect from LH or RH bottom leg
- Concealed wiring kit included
- All fixing accessories included

- 110watts, 230-240 Volts,50 Hz single phase
- Class 1 appliance requires an earth connection
- Ingress Protection Rating IP45 Splashproof











Executive Square

Product Code HTR-TS0601

Dimensions (mm) 520(w) x 680(h) x 120(d)mm


Width Centres 490mm Vertical Centres 480mm



Features

- 6 bars
- Dual wired-can connect from LH or RH bottom leg
- Concealed wiring kit included
- All fixing accessories included

- 50watts, 230-240 Volts,50 Hz single phase
- Class 1 appliance requires an earth connection
- Ingress Protection Rating IP45 Splashproof









Executive Square

Product Code HTR-TS0602

Dimensions (mm) 850(w) x 680(h) x 120(d)mm


Width Centres 820mm Vertical Centres 480mm



Features

- 6 bars
- Dual wired-can connect from LH or RH bottom leg
- Concealed wiring kit included
- All fixing accessories included

- 80watts, 230-240 Volts,50 Hz single phase
- Class 1 appliance requires an earth connection
- Ingress Protection Rating IP45 Splashproof









Executive Square

Product Code HTR-TS0801

Dimensions (mm) 600(w) x 920(h) x 120(d)mm


Width Centres 567mm Vertical Centres 720mm



Features

- 8 bars
- Dual wired-can connect from LH or RH bottom leg
- Concealed wiring kit included
- All fixing accessories included

- 80watts, 230-240 Volts,50 Hz single phase
- Class 1 appliance requires an earth connection
- Ingress Protection Rating IP45 Splashproof









Executive Square

Product Code HTR-TS1101

Dimensions (mm) 600(w) x 1280(h) x 120(d)mm

Width Centres 567mm Vertical Centres 1080mm



Features

- 11 bars
- Dual wired-can connect from LH or RH bottom leg
- Concealed wiring kit included
- All fixing accessories included

- 80watts, 230-240 Volts,50 Hz single phase
- Class 1 appliance requires an earth connection
- Ingress Protection Rating IP45 Splashproof

